



# COMMERCIAL METAL STUD FRAMING

By Ray Clark



Buy this complete title here: <https://bit.ly/463WjAc>

# Commercial Metal Stud Framing

by  
Ray Clark



**Craftsman Book Company**

6058 Corte del Cedro, Carlsbad, CA 92011

Buy similar Craftsman Book Co. titles here: [www.Craftsman-Book.com](http://www.Craftsman-Book.com)

## Acknowledgments

*I would like to take this opportunity to thank my family for their love, guidance, support — and for believing in me.*

Mom, Julie, Uncle Richard, Johnny Boy, Margie Dale, Camilla, Jesse Ray, Amanda, Gary  
*And my friends and associates, who encouraged me, taught me, gave me opportunity, worked with me to bring this book into being, and most of all, accepted and befriended me when I most needed it.*

Jerry & Trish Anderson, Kathy Armbuster, Dick Barker, Larry Barnes, Bob Bernsen, Rob Bigley, Jake Boyle, Hank Bomberry, Joe Buntyn, Keith Buster, Pat Cantu, John Chambers, Kelly & Angie Crow, Garland “the Kid” Curry, Steve Dechant, the people at Deming Photo Lab, Ronnie Everett, Mike Farrell, Dave Greening, John Haley, Ed Hampe, Brian Hetzel, Jim Hilton, Dwayne Kapple, Mike Kelly, Ray Kemple, Dwayne Kruger, John Landers, Gary Lowe, Jim Matt, Chris Mobley, Rick Nienke, Steve Nienke, Ol’ Smoke, Terry Pierce, Billy Phillips, Mark Rivera, Steve Rucker, Troy Schremmer, Terry Shaw, Rod Simms, Jack Wedge, Brett Wiggins, Don Williams, Craig Willnerd, Mike Wilson.

---

## Dedication

*This book is dedicated to the memory of my mother, Berna Mae Clark,  
to Jerry Deutch, a great boss who was loved and is missed by all  
and to God  
for His gifts of forgiveness and perseverance.*

### Looking for other construction reference manuals?

Craftsman has the books to fill your needs. **Call toll-free 1-800-829-8123**  
Visit our Web site: <http://www.craftsman-book.com>

### Library of Congress Cataloging-in-Publication Data

Clark, Ray, 1961 -

p. cm.

Includes index.

ISBN 1-57218-079-X

ISBN 978-1-57218-079-6

1. Steel framing (Building)--Handbooks, manuals, etc. I. Title.

TH2301 .C53 1999

624.1'773--dc21

99-050302

©1999 Craftsman Book Company

Cover design: **Jennifer Johnson**  
Interior Design: **Sybil Ihrig, Helios Productions**

Online Preview



<b>SECTION II: STEP-BY-STEP METHODS</b>		<b>75</b>
<b>5</b>	<b>Interior Walls</b> . . . . .	<b>77</b>
	Walls to the Deck . . . . .	78
	Freestanding Walls . . . . .	86
	Chase Walls . . . . .	90
	Arches . . . . .	91
<b>6</b>	<b>Hollow Metal Jambs</b> . . . . .	<b>95</b>
	Clips . . . . .	96
	Door Jambs . . . . .	97
	Window Jambs . . . . .	102
<b>7</b>	<b>Furred Walls</b> . . . . .	<b>105</b>
	Furring with DWC . . . . .	106
	Furring with 1 <sup>5</sup> / <sub>8</sub> -Inch Studs . . . . .	109
	Furring with Z-Channel . . . . .	111
	Resilient Furring Channel . . . . .	112
<b>8</b>	<b>Structural Stud Walls</b> . . . . .	<b>115</b>
	Bearing Walls . . . . .	116
	Structural Stud Walls with Slide Clips . . . . .	120
	Structural Stud Walls Welded to the Red Iron . . . . .	123
	Parapet Walls . . . . .	123
	Parapet Walls Framed to the Red Iron . . . . .	126
	Diagonal Cross Bracing . . . . .	127
<b>9</b>	<b>Fire-Rated Walls and Ceilings</b> . . . . .	<b>129</b>
	Shaft Liner Systems . . . . .	130
	Fire-Rated Walls . . . . .	136
	Fire Ceilings . . . . .	138
<b>10</b>	<b>Columns</b> . . . . .	<b>141</b>
	Full-Framed Columns . . . . .	142
	Framing a Cornice to the Column . . . . .	144
	Speed-Framed Columns . . . . .	146
<b>11</b>	<b>Soffits</b> . . . . .	<b>151</b>
	Spanning Speed Soffit . . . . .	152
	Suspended Speed Soffit . . . . .	155
	Framed Soffit . . . . .	158
	Framing a Drop with Jigs . . . . .	161
	Suspension Walls . . . . .	166
<b>12</b>	<b>Suspended Drywall Ceiling Systems</b> . . . . .	<b>171</b>
	Suspended Drywall Ceilings . . . . .	172
	Hard Lid Ceilings . . . . .	177
	Skylights . . . . .	179
<b>13</b>	<b>Drywall Methods</b> . . . . .	<b>183</b>
	Marking Sheets with Tape Measure and Pencil . . . . .	184
	Cutting Drywall . . . . .	184
	Setting an Outside Corner with a Rip . . . . .	187
	Screwing Off the Drywall . . . . .	187
	Tying in Slap Studs . . . . .	189
	<b>Glossary</b> . . . . .	<b>191</b>
	<b>Index</b> . . . . .	<b>197</b>

# SECTION I

---

## Tricks of the Trade

**W**elcome to the world of metal stud framing. My name is Ray Clark and I'll be your guide to this challenging and rewarding trade. I've been working in the metal stud and drywall trades for 15 years, and have taught these trades as a Junior College instructor. While teaching, I contacted publishers from coast to coast looking for a text to use in my class. I couldn't find one. So I started writing one for my class — and it evolved into this book.

To keep the information simple, to the point, and useful for both journeyman wood carpenters and apprentices alike, I've organized the book into two sections. The first, Tricks of the Trade, focuses on the unique methods and techniques common to the metal framing trade. The second, the Step-by-Step Methods section, concentrates on the process and flow of work involved in framing metal stud walls, ceilings and soffits. As we work through each chapter, I'll also introduce you to tools that are common to the trade, but which may be new to you.

We'll cover the many advantages of framing with metal studs as opposed to the traditional wood. The most obvious is that metal studs won't burn, rot or become a termite buffet. Structurally, as in bearing walls, metal studs are many times stronger than wood studs, greatly reducing the amount of materials needed to support the load, as well as the amount of time it takes to frame the job. And the fact that you screw metal studs together as opposed to nailing wood studs also makes them stronger and faster to assemble. The metal stud material doesn't dry out, either, so warping, bowing and twisting aren't problems. That lets you build straighter walls and flatter ceilings.



And here's another advantage. Wood prices are jumping all over the place. You can bid a job in January, based on lumber prices at that time, then get a nasty surprise when you get the job and order the lumber in February. Maybe you'll find an owner who's sympathetic and understanding about your request for more money. But probably not. I never have. Steel, on the other hand, remains pretty stable. Weather, politics, overharvesting, environmental issues, rarely come into it. Plus, you don't have to worry about quality. Twenty gauge steel is 20 gauge steel, no matter where it comes from. With wood, especially lately, you never know what you'll get.

Commercial metal stud projects range from small, tenant finish jobs that'll only take a few hours to frame up, to extremely large project that often last for a year or more. Most metal stud contractors, whether union or not, will pay by the hour, with wages ranging from a low of \$7 in some areas of the country to \$20-plus, depending on your experience, in others. Many contractors also offer benefit packages including health insurance and 401(k) plans, as well as paid vacations and holidays.

In this section we'll discuss some commonly-used tricks of the trade in metal stud construction. They're shortcuts and methods that have become standards of this trade. Obviously, knowing the tricks of the trade gives you an edge. First, it'll reduce the time

it takes you to reach journeyman status. Second, you'll know "what's going on" when you begin working with a new partner or new outfit. In either case, the result is the same. It'll help you become more proficient, which makes you a better hand, which means you earn more money. Isn't that the reason you bought this book?

Consider this section as a reference guide that lets us cover the principles of metal stud construction without getting sidetracked on the details of how to accomplish each particular step. This is general knowledge you need under your belt before you actually begin putting up metal stud walls. If you're already an experienced wood carpenter, you may know some of this already. If that's the case, skim through any familiar material in this first section. But I don't recommend skipping anything entirely. You never know when you might pick up a new idea or improved method. It's probably worth your time to read these first four chapters just in case there's a trick or technique that's new for you. And I'll bet there is. Nobody knows it all — not even the authors of books about it.

As you put these methods to work, experience will quickly teach you in where you can put them to work. You can also use this section as a reference guide in connection with the step-by-step directions in the second section of the book.

## C H A P T E R

1



# Wall Methods

## Reading the Blueprints


**R**eading blueprints and layout are subjects too large for us to cover thoroughly here. There are many books available about both subjects. I'll only cover the fundamentals of layout work and blueprint reading to give you a basic understanding. Experience will teach you much more. If you need more information, look at the order form in the back of the book for *Blueprint Reading for the Building Trades* and *Building Layout*. In this chapter, I'll just cover the basics of print notations.

The *magnetic north arrow*, shown in Figure 1-1, is located on the right-hand side of each page of the prints. It helps keep all of the work on the job site going the same direction.


The *detail symbol* indicates a specialty item or condition in a wall, and gives the location of a detailed drawing for the item. The detail symbol in Figure 1-2 refers the reader to detail A (top letter) on page A2.4 (bottom number). The detailed drawing is often called a *cut*.

The *wall legend*, also known as a *key* (Figure 1-3), distinguishes the various wall types in the prints. Each wall type in the legend





**Figure 1-1.** This shows a north or “magnetic north” arrow which points to true north, and helps keep everything going in the same direction.




**Figure 1-2.** This detail symbol is directing the carpenter to a detail (or cut) “A” on page A2.4 in the prints.

has a detailed description and a number. The wall numbers in the legend coincide with wall numbers in the floor plan. The wall legend tells you what type of metal stud framing material you’ll use for each wall. It also lets you know whether the wall is freestanding or framed to the deck. If it’s a freestanding wall, it also gives you the required height. The wall legend also indicates the thickness, type and the number of layers of drywall used, and any insulation materials.

The *reflective ceiling* section of the prints (Figure 1-4) gives all the ceiling elevations and the material they’re to be built of. Rooms that show light grid lines have a grid ceiling, while clear rooms have a drywall ceiling. The dimensions and elevations for soffits are also given in the reflective ceiling plans, as well as the location of recessed lights and HVAC vents in the ceiling. All elevations are finish elevations, so you’ve got to add the thickness of the drywall to achieve the frame line elevation.

## The 3-4-5 Squaring Method


Let’s begin with one of the most basic tricks in construction—making a right angle that’s exactly 90 degrees. If you can’t do that, you’ll create problems that will affect not only your work, but that of all the trades that follow you.



**Figure 1-3.** This wall legend uses Roman numerals to distinguish the different types of walls on the job.



**Figure 1-4.** The reflective ceiling plan shown here breaks this floor of the building into “grid ceilings” and “hard lids.” You can also see a large stair-step drop in the entry way in the rectangle grid near the bottom of the plan. The lines around the rectangle show the separate widths of the stair-steps. The detail symbol cutting through the drop will give the rest of the information.



**Figure 1-5.** The squaring method begins with marking first the starting point on the chalk line, then the 3-foot point.

The 3-4-5 method is a simple way to square a perpendicular line off an established wall or reference line using only your tape and pencil. It's accurate, it's easy and it's faster than setting up a transit or laser to do the same job. There are five steps in this method:


**Step 1** Mark a crow's-foot anywhere along the reference line (see Figure 1-5). That's your starting point for the squaring process.

**Step 2** From the first crow's-foot, measure straight down the reference line 3 feet and mark a second crow's-foot.


**Step 3** From the 3-foot mark, measure 4 feet off the reference line, as close to 90 degrees as possible, and strike an arc approximately 1 foot long (shown in Figure 1-6). As you draw the arc, hold the tape measure to the crow's-foot on one specific edge of the tape. To ensure accuracy, you've got to hold the pencil on the same edge of the tape while striking the arc. Striking the arc is easiest as a two-man job. But if there's no help close by, drive a concrete pin into the pivot point and hook the end of your tape to the pin.

**Step 4** Return the end of your tape measure to the first crow's-foot marked on the reference line, and from there strike a second, intersecting arc at 5 feet (see Figure 1-7).

**Step 5** Next, pull a chalk line from the 3-foot crow's-foot on the reference line, through the point where the two arcs intersect (Figure 1-8). Pull the chalk line quite a ways past the intersecting arcs.



**Figure 1-6.** Measuring from the 3-foot mark and striking an arc at 4 feet, using the same edge of the tape at both points.



**Figure 1-7.** With the end of the tape anchored at the starting point, strike the 5-foot arc intersecting with the 4-foot arc.



**Figure 1-8.** Pulling the chalk line from the 3-foot mark through the intersecting arcs completes the 3-4-5 squaring method.




Just be sure you can see the chalk line pulling through the intersecting arcs. To square larger areas, double the 3-4-5 measurements to 6-8-10.

## Laying Out the Walls

Establishing the reference lines and laying out the work area are the first steps in metal stud framing. The layout work is critical to a quality frame job. That's why it's entrusted to only the top hands on a job. The reference line (sometimes called the *gospel line*) is the centerline of the job. All the other wall lines will be established from the gospel line. It *has* to be right.

Establish the gospel line by measuring the overall width of the concrete slab (or pad) at the two opposite ends of the building. Or you can establish the gospel line from the red iron columns to the structural steel. Then mark half of the overall width at each end (Figure 1-9). Next, snap a chalk line from mark to mark. For long slabs, use a laser to make multiple center reference marks so you can snap a consistently straight chalk line. Finally, spray clear enamel over the chalk line to protect it. You want it to last until the layout is complete.

With the gospel line in place, your next move is to establish a perpendicular reference line exactly 90 degrees to the gospel line. You can establish it with a transit or laser, or with the 3-4-5 or 6-8-10 method (as long as you do it carefully and accurately).



**Figure 1-9.** Here you can see the center of an 80-foot slab marked near one end of the pad.

Now check the floor plan section of the blueprints to determine the layout of the wall line. Begin with the exterior walls and then move to the interior, starting on the long walls first. The hallways are a good starting point, for two reasons:

1. They're long continuous walls you can use to establish other parallel wall lines.
2. The hallways are among the few walls on a job that have very little tolerance for variance. The *Accessibility for the Disabled Act* requires you to meet stringent guidelines for width. Bathrooms are another area where wheelchair accessibility is very important, so you don't have much tolerance for these walls either.

As you lay out the wall lines, remember to allow for the thickness of the drywall. Forget this and your walls will be more than an inch short. When the building inspector takes out his tape measure, you're done for! All wall line dimensions in the prints are *finished walls* unless otherwise noted. You have to consider all the thickness of all the layers of drywall. You'll find this information in the *wall legend* section of the prints.

After you've marked the starting walls (exterior walls and hallways), work your way through the job from end to end, snapping all the long walls first. As you figure the wall dimensions, mark them as close to the ends of the wall as possible. Then snap a chalk line between the marks. It's common to add the width of the framing material and snap a line for both sides of the bottom plate (Figure 1-10). This eliminates a common mistake: plating the wrong side of a wall line. Snapping a chalk line to both sides of a wall also makes it much easier to mark the next wall, since you measure it from the wall you just completed. If you don't snap both



sides of the plate, always mark an “X” on the side of the line where the wall will sit (Figure 1–11).

## Laying Out the Doors and Windows

As you’re laying out the walls, it’s important to lay out doors and windows at the same time, completing each wall as you go. Square the wall lines off on both sides of the door opening and clearly mark the opening *DOOR*. Then write the door number inside the opening and mark the swing of the door (Figure 1–12). Lay out the opening for a door 4 inches wider than the door’s width according to the prints. The dimensions in the door schedule section of the prints are the size of the door itself. You need to add 4 inches (2 inches on each side) for the jamb.

After you’ve chalked the wall lines, go back and lay out the windows. Write the window number between the layout marks, as well as the elevation of the bottom of the jamb. Figure 1–13 shows a properly laid-out window. The window studs are clearly marked right at the wall line. The information (42” off FF 40” x 40”) tells the framer that the bottom of the window jamb is 42 inches off of the finish floor, and the window is 40 inches tall and 40 inches wide.

Every outfit has its own customs, so you won’t find windows laid out like this on every job. It’s also an accepted practice to lay out the window jambs *after* the plate is shot down. In this case, the layout for the window studs is marked along the edge of the plate with the layout for the studs. You can also use this method for laying out items like fire extinguishers and tissue dispensers that are recessed in the wall. Write their elevations inside the plate between the stud layout marks. You’ll find items recessed in a wall noted in the prints on the wall line with a *detail symbol*.

It’s important to maintain consistency in the window and door jamb elevations. It’s common to find an unlevel or poorly-floated pad that causes the top elevation of the jambs to be uneven. In most cases, the jambs should have a common elevation throughout a given work area. If they don’t, it’ll be noticeable when the room’s finished—and then it’s too late. Make bench marks with a water level or transit, or use a laser to make sure they’re consistent.

## Layout Around an Obstacle

What if there’s an obstacle that prevents you from snapping a chalk line on the wall line? Here’s a four-step method you can use to extend an accurate chalk line around any obstructions.

**Step 1** From a reference or wall line, measure out and mark two crow’s-foot marks as far apart as possible.



**Figure 1–10.** In this example you see an intersecting  $3\frac{5}{8}$ -inch wall line laid out with both sides of the wall snapped.



**Figure 1–11.** One side of a wall line snapped out with X’s marking the side of the line the wall will sit on.



**Figure 1–12.** A door laid out along the wall line with the door number and swing marked out in the door opening.



**Figure 1–13.** The rough opening for a window laid out along the wall line, telling the carpenter that the window R.O. is 42 inches off the finish floor and 40 x 40 inches.



**Step 2** Hold the end of the chalk line down to the first crow's-foot, then pull the chalk line past the second crow's-foot, as far as you can accurately line up the chalk line on the crow's-foot (Figure 1-14).

**Step 3** While you hold the chalk line tightly to the first crow's-foot, your partner will wrap the opposite end of the chalk line around a flat carpenter's pencil to keep it raised slightly off of the floor (Figure 1-15). Then your partner can adjust the chalk line until it's positioned directly over the second crow's-foot (Figure 1-16). If your partner is so far away from the second crow's-foot that he can't accurately set the chalk line to the crow's-foot, you'll need a third person to help. The third person will also hold the chalk line down to the floor in the center after it's adjusted into place, and snap the chalk line on each side.

**Step 4** Check the line just snapped for accuracy by looking to make sure that the chalk line came exactly through the crow's-foot. If the chalk line is off, even slightly, erase it and start over again with a different color of chalk. If the line is off by  $\frac{1}{4}$  inch in 10 feet, it'll be off by  $\frac{1}{2}$  inch in 20 feet. It's surprising what trouble a  $\frac{1}{2}$  inch can make.

## Plumbing with the Plumb Bob

The plumb bob is a very simple, accurate and quick way to transfer a wall line from the floor to the deck. Make sure the plumb bob has a string line that's braided, not wound. That helps prevent the plumb bob from spinning excessively. Here are some common techniques for plumbing up.

The first step in the plumbing process is to adjust the elevation of the plumb bob, so the tip is between  $\frac{1}{8}$  and  $\frac{3}{8}$  inch above the floor or edge of the plate. A quick way to achieve the desired elevation is to lace the plumb bob string through the fingers of your hand holding the plumb bob. Run the string line over your little finger, then under the ring and middle fingers, and over the index finger to the thumb (Figure 1-17). The thumb will hold the string line tight to the deck or other surface you're plumbing to. When you release pressure on the thumb, it's easy to raise and lower the plumb bob, with control.



**Figure 1-14.** In this example you see the chalk line being pulled well past the far crow's-foot, and adjusted to the crow's-foot.



**Figure 1-15.** Wrapping the chalk line around your pencil not only keeps the chalk line off the floor as it's set to the crow's-foot, it will also keep the line straight over humps in the slab.



**Figure 1-16.** Here the chalk line has been set and is ready to snap.



**Figure 1-17.** The string line of a plumb bob properly run through the fingers and held to the deck with the thumb. Notice that both the wall line plumb point and a 90-degree plumb mark were marked.

The tip of the plumb bob must be steady to get an accurate reading. To steady the tip, your partner will place both hands close together on the floor, one hand on each side of the plumb bob. By raising the index finger of each hand to the tip, with light and equal pressure, he can steady the plumb bob (Figure 1-18).


In directing the movement of the plumb bob, use clear concise terms like “left an eighth” or “right a quarter.” These directions are quicker and easier to understand when they’re coupled with hand signals. Once plumb is achieved, sing out loud and clear. Don’t leave your partner guessing about what’s going on.

On the deck, make two crow’s-foot marks at the exact point of the string line, one mark in the same direction as the wall line below, the second mark at 90 degrees to the wall line. You can see these marks in Figure 1-17. Also mark the 90-degree point at the bottom plate or wall line. The 90-degree plumb marks will be used later as a reference mark. From this reference mark, transfer the layout marks for the studs from the bottom plate to the top plate. You can also use the plumb marks to establish perpendicular wall lines by measuring from the reference mark to the perpendicular wall line. Then transfer the measurement to the deck above (Figure 1-19).


The pocket laser is a great advance in carpentry tools. These battery-powered lasers are accurate to about 50 feet, and allow one person to do the plumbing work. Bump the laser up to the plate and measure from the laser beam 1 inch to the plate line, as shown in Figure 1-20. The laser can also be set right to the wall line,



**Figure 1-18.** Steadying the tip of the plumb bob with light, even pressure from each index finger.



**Figure 1-19.** Measuring from the 90-degree plumb mark to establish the stud layout at the top plate.



**Figure 1-20.** A pocket laser set up against the bottom plate of a  $3\frac{5}{8}$ -inch wall. While the wind and vibration will affect the pocket laser to a certain extent, it’s still much faster and easier to use than a plumb bob. Use caution, though; never look directly into the beam. It can damage your eyes.



matching the hash marks on the laser to the chalk line. These little lasers also shoot a level beam, and both the plumb and level beams form a square 90-degree angle.

## Cutting Plate and Studs by Hand

There are two ways to cut your metal plates and studs: with snips or by scoring them. We'll start by cutting with snips.

### Cutting with Snips

To begin with, let me make a couple of recommendations. First, *always* wear leather gloves while working with metal stud material of any kind. (The carpenters in our examples aren't wearing gloves to give you a clear view of the work being done.) Second, if you're going to start with just one pair of the snips used in the trade, I recommend the straight cuts. The snips are available in three different directional cuts. Red-handled snips cut left, green-handled snips cut right, and yellow-handled snips cut straight. You'll have to choose the snips that are most comfortable for you. Eventually, you'll probably want to have all three cuts.

Cut light gauge (25, 22 and 20 gauge) studs and plate in two smooth fluid moves. But this smooth fluid movement comes with experience. We'll break the cutting process into three steps:

**Step 1** Measure out and mark the length of the cut, marking the cut with your snips instead of your pencil (Figure 1-21). This eliminates the time spent switching the pencil for the snips. But be careful not to cut your tape measure—especially if someone's watching!

**Step 2** Square the cut from one leg, across to the other leg of the material. Whenever possible, eyeball the cut across from one leg to the other. Eyeballing cuts is an important skill that you need to master as quickly as possible. Sight through the cut in the first leg of the stud to the other leg, and cut it with your snips (Figure 1-22). Mastering this step takes practice. Use some scrap stud to work on until you can make the two cuts and fold the material back over with the edges lining up evenly. The stud in Figure 1-23 has a perfect square cut. While this is the ideal, there's usually some room for error. If the situation calls for a perfectly-square cut, use a speed or combination square to mark the cut (Figure 1-24).

**Step 3** Fold the material back at the cuts you made in the two legs, then unfold the material. Using your free hand, grab one side of the material 2 to 3 inches from the



Figure 1-21. Marking the length of the cut with snips.




Figure 1-22. Eyeballing across the stud from the first cut to the second.



Figure 1-23. A stud cut square, using snips. You can tell if the cut is square by folding the stud back over and making sure the edges of the stud line up.




Figure 1-24. The cut point squared across the hard side of a stud with a speed square, with one leg of the stud cut to the squared line.



cut. Next, cut across the fold line in the material. As you're making the cut, grip the material tightly so it rolls out of the way of the cut (Figure 1-25). Rolling the side of the stud out of the way will allow the snips to pass through your material and complete the cut.

## Cutting by Scoring

Use this method to cut heavy gauge material using only hand tools. It's particularly useful when there's no chop saw available, or it's in use. The procedure is similar to cutting with snips, so I won't go into great detail.

**Step 1** After marking the length of the cut on the hard side of the stud in pencil, set your speed or combination square to the mark. Using your utility knife, score the hard side of the stud, two to four times depending on the sharpness of the knife blade. Make certain that your hand is above the direction of the cut, and that your body is positioned to the side of the cut (Figure 1-26).

**Step 2** Using your snips, cut the legs of the stud at the score. Heavy gauge bullnose cutters are the ideal snips for cutting structural material, or keep an old pair of snips around for this purpose. That prevents your good snips from being trashed.

**Step 3** After completing the cut, fold the stud back and forth a few times until it breaks along the score.

## Splicing Plate

Splicing plate (or *track*, as it's also called) is the common way of joining the sticks of plate to form one long continuous piece. You'll have to splice the plate in many situations, including the top and bottom plates of walls, and in suspension systems like soffits and suspension walls, to name just a few. Unless you're framing in an expansion, everything has to tie together. Tying the metal stud framing together provides much of its strength. I'll break the process into steps to describe it, but when you do it in the field, it'll become a fluid movement.

1. Using your snips, cut a 1-inch to 1<sup>1</sup>/<sub>2</sub>-inch-deep slice in the hard side (back) of the plate, as shown in Figure 1-27. Keep in mind that the cut for the splice is always made in the next piece of plate to be set in place.
2. Next, place the splice against the end of the plate already shot in place. Figure 1-28 shows two sticks of



**Figure 1-25.** The scrap side of the stud rolls up out of the way if you grip it tightly, allowing the snips to easily pass through the cut.



**Figure 1-26.** Using a speed square to "score" a 6-inch structural stud with a utility knife. The stud sometimes needs to be scored several times. The better it's scored, the quicker it will snap off when you fold it back and forth.



**Figure 1-27.** Cutting the slice in one end of a stick of 3<sup>5</sup>/<sub>8</sub>-inch plate, using snips.





bottom plate being spliced correctly. Leave the end of the first stick loose so you can slide the two pieces together. The splice also acts as a third hand to hold up one end of the plate while you slip it onto the studs in suspension work. Figure 1-29 shows this happening while plating the top of a freestanding wall. Any time you're plating the bottom of the studs in a soffit or suspension work, clamp the splice together. In Figure 1-30, the plate is clamped right in the corners to prevent any offsets in the plate — either in and out or up and down. Tack the splice together with only one framing screw, then add more screws to the other side and bottom of the plate as you set it to the string line. This prevents kinks from forming at the joints of the plate.

3. In walls running from floor to deck, hold the spliced joints cut into the top and bottom plate to the wall line and shoot them in place (Figure 1-31). As you can see, the ends of the plate are spliced and then shot down with one pin. This technique creates one continuous length of plate while saving one pin and load per joint.

## Splicing or Scabbing Structural Plate

To splice structural plate, follow the same steps, except you'll make the splice with a chop saw or your old pair of snips. (Making cuts on structural material with your good pair of snips will make them an old pair real quick.) The problem you'll have with splicing the heavy gauge material is that the material's thickness may cause a bump in the finish material. In some situations you can get by with this, but in others you can't. The type of finish material will dictate your splice. When a splice won't work for you, scab the plate together. A scab is simply a scrap piece of stud cut from the same width material as you're using to frame the wall. Scab the plate together following these steps:

1. First, cut the scab about 6 inches long, so each piece of plate has roughly 3 inches of the scab to screw into. Slide the scab into the first stick of plate already in place, and clamp in the corners. Then fasten the scab




Figure 1-28. Two sticks of bottom plate being spliced together.




Figure 1-29. The splice will hold up one end of the top plate in this freestanding wall.



Figure 1-30. A joint in the plate is clamped directly in the corners of the plate.



Figure 1-31. The ends of two sticks of bottom plate spliced together and shot down with one pin.



**Figure 1-32.** Here a scab is clamped and screwed off into the first stick of 6-inch structural plate, forming the joint. Wider 6-inch deflection plate was used in this example to highlight the scab itself.

in place with one self-drilling framing screw (commonly referred to as an S-12 or pan head), as shown in Figure 1-32.

2. Now, slide the next piece of plate onto the scab as it's slipped onto the studs. Then clamp and fasten it in place with one S-12. The two screws will hold everything together until you straighten the wall with a string line. Then run three more screws in each side of the scab.


## Shooting Down the Bottom Plate

As you shoot down the bottom plate (fasten it in place with a powder-actuated nail set), it must follow the wall line precisely. Plate that doesn't follow the wall line will create dips and bumps in a wall that may make the wall unacceptable. In situations where only one side of the wall line has been snapped, shoot the plate down on the side of the wall line marked with an "X," as shown in Figure 1-33.

You'll splice light gauge plate at the joints as you shoot it down. With heavy gauge plate, you can simply butt the ends together at the joint (Figure 1-34). Space the pins approximately 24 inches apart in either case, as shown in Figure 1-35.



**Figure 1-33.** Bottom plate shot down following the wall line with the plate sitting on the side of the wall line marked with an X.



**Figure 1-34.** Bottom plate on a 6-inch structural stud wall butted together and shot down.



The bottom plate runs continuously under windows and other wall penetrations. As you shoot it down, transfer any layout information for these items from the wall line to the plate with a black felt tip marker. At door jambs and wrapped openings, stop the bottom plate  $\frac{1}{8}$  inch short of the opening (Figure 1-36). The exception to this rule is when you're installing a computer floor. In that case, the bottom plate runs through the door jamb's rough opening. We'll look at this situation in detail in Chapter 7.

Sometimes the bottom plate will be interrupted by obstacles in a wall line, such as plumbing lines and large conduit. In the plumbing walls (chase walls) of bathrooms, for example, you may have to piece in the bottom plate (Figure 1-37).

As you shoot down the bottom plate, establish the sliders (or slap studs) at intersecting walls and inside corners. Frame the slider into the shorter walls, so that they tie into the longer wall of the corner. That's important because it allows a  $\frac{3}{4}$ -inch gap between the two pieces of plate that form a corner in the metal stud walls. The gap allows the drywall to slide inside the corner. Then, as the walls are rocked, the slider is tied into the drywall to form a solid corner. There are two common types of corners:

1. The *inside/outside corner* is shown properly plated in Figure 1-38. This corner is a widely-accepted method of plating an inside/outside corner.
2. The *double inside corner*, formed by a partition wall tying into a long wall (such as a hallway), is shown properly plated in Figure 1-39.

Shooting down the bottom plate is a two-man job. As one carpenter makes any needed cuts, including splicing the plate and putting it in place along the wall line, his partner follows behind setting the plate to the wall line and shooting it in place.


While you're shooting the plate in place, there'll be some changes or mistakes that'll make it necessary to pull the plate back up. To get the pins loose quickly and easily, you can shoot them loose with the shotgun. Using the shotgun with no pin in it, set the barrel right on top of the pin you want to pop loose, and fire. The piston in the shotgun will drive the pin on



**Figure 1-35.** You can see the first stick of bottom plate shot down for a  $3\frac{5}{8}$ -inch wall with the pins staggered from side to side every 24 inches. Notice the end is left loose so the next stick can be spliced to it.




**Figure 1-36.** The bottom plate of a  $3\frac{5}{8}$ -inch wall stopped for both a corner and a door.



**Figure 1-37.** Here's a good example of a congested plumbing wall that required a header at the bottom of the wall to get around an obstacle.



**Figure 1-38.** Here we see the bottom plate of a  $3\frac{5}{8}$ -inch wall forming an inside/outside corner, leaving a  $\frac{3}{4}$ -inch gap for the drywall to slide inside the wall.



**Figure 1-39.** A  $\frac{3}{4}$ -inch gap left open between the bottom plate of two intersecting walls, forming a double inside corner.

through the plate into the concrete. Never use this technique when the pins are shot into steel. Instead, grab the pin shot into the steel with your end nippers and work the pin back and forth until it comes loose.

## Shooting Up the Top Plate

When you start shooting up the top plate, you might expect that you could simply learn a few standard procedures and get to work. That's true—up to a point. The standard procedures will carry you through the “gravy” work. But you need more than that. We'll cover the basic principles of plating the deck, *and* the deck conditions you're likely to find which will complicate the process. You need to know what problems to look for, and how to overcome them.

### The Basics

The basic methods for plating the deck are a lot like those for shooting down the bottom plate. Shoot the plate to the deck with a gas- or power-actuated nail set, following the wall line exactly and spacing the pins approximately 24 inches apart. The splice plays an additional role with the top plate. You can use the splice to hold up one end of a stick of plate as you fasten the opposite end in place.

The top plate follows the bottom plate's slider (slap stud) placement, with the same  $\frac{3}{4}$ -inch gap (Figure 1-40) to allow the drywall to slide inside the intersecting wall at inside corners. The outside corners are also determined by the bottom plate, using the 90-degree plumb mark to establish the corner points and the stud layout for the wall. Run the top plate continuous unless there are obstacles that prevent it. Stop the top plate at all wall expansions, leaving a  $\frac{3}{4}$ -inch void in the plate. Plumb the wall expansion from floor to deck.

### Concrete Decking

Concrete decks are typical in multistory buildings. They're formed of raw concrete, corrugated metal decking with concrete poured on top of it, or a prestressed concrete truss system (Figure 1-41). You can fasten the plate to any of these



decks with a gas- or powder-actuated nail set. But don't shoot into corrugated metal decking until you've checked that the concrete has been poured. If you shoot a pin to unpoured metal decking, it won't hold the plate in place. It also poses a serious safety hazard. In this situation, screw the plate to the deck using S-12s. If the deck is concrete trusses, you may have to span them with studs that have tabs cut on the ends. Shoot them to the bottom of the ribs, then screw the top plate to the studs.

## Metal Decking


In a single-story commercial building like department stores and malls, corrugated metal decking is commonly used as the roofing material. Screw the top plate to the deck with S-12s. But there are two common problems.

First, the long decking screws used to fasten down the roofing materials often come through the decking in the wall line. They're in the way of the top plate. To solve the problem, snap off the screw close to the deck (Figure 1-42). Simply grab the screw close to the deck with your lineman's pliers and bend it until it breaks off.

Second, the top plate may line up inside the concave groove of the corrugated metal decking. That makes it difficult to attach the plate to the deck, as well as to fasten the studs into the plate later. To solve the problem, cut short pieces of plate with tabs and screw them to the deck spanning the concave groove. Space the bridging 24 inches on center and screw it to the decking with S-12s, or shoot it up if the decking has concrete poured on top. Once in place, plumb and snap the wall line to the bridging. Then fasten the top plate to the bridging with S-12s or tek screws (Figure 1-43).

## Plating to the Bar Joist

In some framing situations, it's acceptable to attach the top plate to the bottom of the bar joist (a structural steel roofing and flooring joist). See Figure 1-44. There are two advantages to doing this. First, it eliminates the need to plumb up the wall line between each set of bar joists. Second, because the studs will only run up to the bottom of the bar joist.



**Figure 1-40.** Here you can see the top plate fastened together using the tab method. The plate is cut, leaving a  $\frac{3}{4}$ -inch gap to allow the drywall to pass through the wall.



**Figure 1-41.** This prestressed concrete truss system supports the floor above.



**Figure 1-42.** Grab a long decking screw near its base with lineman's pliers and bend it over, snapping it off.



The type of fastener you'll use to fasten the plate to the bar joist depends on the bar joist's hardness. In some cases you can use S-12s, as long as they take to the bar joist without stripping out. If the bar joist is too hard to use S-12s, use a powder-actuated nail set to fasten the plate in place. When you use a shotgun to fasten the plate to a bar joist or any part of the red iron superstructure, always use steel pins. Shoot the pins into the bar joist close to the angle (inside edge) in the steel (Figure 1-45). Shooting the pins near the outside edge will cause the bar joist to bend under the force of the shotgun.

While you're plating the bar joist, use clamps to hold the plate in place on the wall line as you're shooting it to the bar joist. That prevents the plate from slipping — or even falling — as it's shot to the bar joist. You can avoid having to drop a plumb bob to establish the outside corner by using the 90-degree plumb mark we discussed earlier. Outside corners will often fall between two bar joists. To make a strong corner, run the top plate on past the actual corner point to the next bar joist, then fasten it as shown in Figure 1-46. Later in the chapter I'll cover how to form the corners.

When you're framing a fire, smoke or sound wall to the bottom of the bar joist, it must continue to the deck. As you stuff the studs (install them into the plate), cut scrap stud or plate to fit in between the bar joist, then fasten it to the deck. To continue the wall line up to the deck, set a straightedge, either a drywall rip or a level, to a wall stud and slide it up to the deck. Then mark the wall line, as shown in Figure 1-47.

## Forming a Corner with Plate

There are two basic skills every metal stud framer needs:

1. The ability to determine the type of corner you'll need in a given situation
2. The ability to quickly and correctly cut the plate for the corner you've chosen



**Figure 1-43.** The concave grooves in a corrugated metal deck spanned with tabbed plate. The top plate of a 3<sup>5</sup>/<sub>8</sub>-inch wall is screwed in place to the spreaders.



**Figure 1-44.** The top plate of a 3<sup>5</sup>/<sub>8</sub>-inch wall screwed to the bottom of the bar joist using S-12s (self-drilling framing screws).



**Figure 1-45.** Here we see a pin shot right at the bend point of the angle iron at the bottom of the bar joist.



**Figure 1-46.** The top plate of a  $3\frac{5}{8}$ -inch wall run past the actual corner point to the next bar joist and shot in place, with the top plate of the intersecting wall tabbed and set in place.



**Figure 1-47.** Using a 4-foot magnetic level to continue the wall line on up to the deck. If you look closely you can see the bottom of a stud up on the floor above.

Here we'll take a look at four common methods of forming a corner with both plate and utility angle. Each style of corner is useful in certain framing situations.

### Top Plate Outside Corners

To form this type of corner, begin with the first of the two intersecting plates fastened in place along the wall line, with the end roughly  $\frac{1}{4}$  inch short of the actual corner point. As you

form the corner, notch the first stick of plate for the intersecting wall that'll form the corner. Measure back from the end of the plate a distance equal to the width of the material you're using, plus  $\frac{1}{2}$  inch. Cut the inside leg of the plate with your snips and fold the cut material up out of the way (Figure 1-48).

Now set the end of the plate up to the corner, overlapping the end of the plate already fastened in place. That holds up one end of the plate while you clamp the opposite end in place to the wall line. Eyeball the end of the plate to within  $\frac{1}{4}$  inch of the actual corner point (Figure 1-49). Make any needed adjustments, then fasten the plate in place. In freestanding or suspended conditions, screw the corner together using three framing screws. You'll find this technique useful when framing to bar joist and freestanding walls, and also when framing to the deck. You'll also use it for capping jigs and parapet walls.

### Intersecting Walls


There are two common types of corners for intersecting walls, depending on whether the two walls have equal plate elevations.

#### *Walls with Equal Plate Elevation*

You'll use this type of corner for framing an intersecting wall into a long wall that runs past, such as a partition wall to a hallway wall. To form this corner, begin by cutting about a 2-inch tab on one end of a stick of plate. Now set the tab on top of the plate of the wall that's already in place. The tab will support one end of the plate as you position it on the wall line at the other end and stand up a stud to support the top plate. Don't forget to leave a  $\frac{3}{4}$ -inch gap for the drywall to slide through. When the plate's in position, clamp it in place, then fasten it with the appropriate fasteners, as shown in Figure 1-50. This style of corner will work in most situations where the top plates of the two intersecting walls are at the same elevation.

#### *Walls with Offset Plate Elevations*

Use this corner when you're tying together two walls with different plate elevations. After the long wall is framed, figure out whether the new wall line will hit a stud or fall between two studs. If it hits a stud, first run a diagonal brace



**Figure 1-48.** The inside leg of the plate is cut and folded out to allow it to overlap.




**Figure 1-49.** You can see the plate set in place overlapping the first stick of plate to form the corner.




**Figure 1-50.** The top plate of an intersecting wall tabbed and screwed in place with four tek screws. The shoe of a kicker is screwed in place right next to the corner joint.

from the top plate to the stud you're going to fasten the top plate to. With the stud plumbed and braced, simply cut a shoe on one end of the plate, and clamp it to the stud at the desired height (Figure 1-51). Slip the opposite end of the



**Figure 1-51.** A shoe cut on one end of the top plate of a shorter intersecting wall is screwed off to a layout stud of a taller wall.



**Figure 1-52.** Here the top plate of the shorter intersecting wall is tabbed and screwed off to a spreader.

plate onto a wall stud that's been screwed off on layout in the bottom plate. This will carry the top plate as you work the wall.

When the wall line falls between two of the layout studs, cut a spreader from scrap stud material with tabs on each end. Use it to span the gap between the studs, using the tabs to fasten the spreader to the wall studs (Figure 1-52). To figure the spreader length, measure between the studs at the bottom plate, minus an additional  $\frac{3}{8}$  inch for play. Put the spreader  $\frac{3}{8}$  inch





higher than the length of the studs used in the wall, and screw it to the wall studs. As you fasten the spreader to the studs, make sure you maintain the 16- or 24-inch stud layout. A temporary diagonal brace from the top plate of the original wall, down to just over the spreader, will hold the new wall plumb (Figure 1-53).

Screw the brace to the top plate and clamp it to the studs over the spreader until you get everything plumb. Here's how to do it. Measure from one of the studs supporting the spreader to the bottom plate of the wall you're framing. From the same stud, measure over and mark the same number on the spreader. Put an "X" on the side of the mark that you'll set the plate to. Now clamp the top plate of your wall to the bottom of the spreader with the edge of the plate on your mark. Just tack the plate in place with one framing screw for now; you'll add another after you've plumbed the other end of the plate. Now the diagonal brace will hold everything plumb when you plumb up the top plate, because the spreader holds the stud and plate. When the tall wall is rocked, tie the slider of the short wall into the drywall and remove the diagonal brace. This technique works well for framing a freestanding wall into a wall that's framed up to the deck.

### ***Tying Into Preexisting Conditions***

To form this type of corner, fasten the first stud of the wall to a preexisting condition, whether it's drywall, concrete, steel or a block wall. Naturally, you'll want to plumb the stud with your level while you're fastening it. In this case, simply screw the top plate to the end stud, securing the corner at the top plate (Figure 1-54). An alternative method is to use a shoe at one end of the plate. Flatten out the shoe and fasten it to the preexisting condition  $\frac{1}{4}$  to  $\frac{3}{8}$  inch higher than the studs used to frame the wall (Figure 1-55).

### **Bottom Plate Outside Corner**

Form this corner like the top plate outside corner. Cut one leg of the plate, but fold in or cut off the excess plate to allow the overlapping (Figure 1-56). This type of corner is often used in suspension walls, jigs and soffits.




**Figure 1-53.** A diagonal brace run from the top plate of a tall wall to just above the spreader and top plate of a shorter intersecting wall. The spreader will be taken off as the tall wall is rocked and the slider is tied in.



**Figure 1-54.** The first stud of this wall was tied into an already-framed and -rocked wall. Then the top plate of this wall was screwed off to the stud to start the wall. The first stud of a freestanding wall like this can also be shot to structural steel or block walls.



**Figure 1-55.** Here's the top plate of a freestanding wall fastened in place using a shoe turned up and flattened out.




**Figure 1-56.** Here the bottom outside corner plate of a soffit is cut and screwed together.

## Laying Out Plate

As you lay out the plate to receive the wall studs, it's important to consider the drywall. Place the studs so the drywallers can hang the rock in a series of full sheets without cutting the drywall or adding studs (Figure 1-57). Since most commercial drywall is hung vertically (stood up) with only 4 feet between joints, it's easy to see how much extra work a poor layout job will cause.

To begin the layout, find the point the first sheet of drywall will butt into, and pull your layout from there. The blueprints will call out the spacing of the studs—either 16 or 24 inches on center. If you're pulling the layout off a wall that's not rocked yet, figure the thickness of all the layers of drywall that will cover that wall. Add that thickness to the layout for the first stud. Then clamp the end of your tape measure to this layout mark with a pony clamp and pull the layout from this point, as shown in Figure 1-58. Because the stud layout is commonly marked at either the centers or the soft sides (open sides) of the studs, it's important to indicate which side of the layout mark the studs will sit on. Figure 1-59 shows how to mark the studs for both centers and the soft side. The "X" beside the layout mark tells you the stud sits on that side of the layout mark. Mark the centers with the centerline symbol.



**Figure 1-57.** An 8-foot sheet of drywall "stood up," breaking perfectly on a structural stud.



Another thing to watch for while pulling layout is to ensure that the drywall doesn't "break" at the edge of door and window jambs. When laying out walls with multiple doors and windows, I recommend pulling an exploratory layout to see where it will hit on the door and window jambs. If the layout hits at unacceptable points around the jambs, burn the necessary number of inches at the beginning of the layout to correct the condition, then mark the first stud layout.

Once you've established the beginning point of the layout, pull layout for the length of your tape measure. Then use a pony clamp to clamp the end of your tape measure to the last layout mark, and lay out the remainder of the wall.

Transfer the layout up for the top plate using the 90-degree reference marks you made while plumbing up the wall line. Your partner will measure from the 90-degree reference mark to the closest layout mark on the bottom plate. Then measure this distance from the 90-degree reference mark at the top plate to establish the first stud layout mark. Because your work area for top plate work is limited to the length of the scaffold, lay out the first stick of plate and stuff the studs simultaneously. Then pull layout from the soft side of the studs for the remainder of the wall.

## Stuffing Studs

Stuffing the stud is a simple, fast-paced step of the framing process. The stuffing process consists of three quick steps. First, insert the stud into the plate diagonally (Figure 1-60), then stand it upright with the stud turned sideways in the plate. Next, slide the stud close to the layout mark, and turn it into place with the soft side (open side) of the stud facing the direction from which the layout was pulled. Finally, tap it into position, exactly on the layout mark, and screw it off.

As you pull the studs out of the bundles and skids (large pallets with several bundles) they'll often be stuck together in pairs. To get them apart quickly and easily, slam the pair of studs on the floor a couple of times. Slamming the studs will jar them apart.



**Figure 1-58.** This picture shows the end of a tape measure set to a layout mark and clamped to the bottom plate while pulling stud layout.



**Figure 1-59.** The bottom plate of a  $3\frac{5}{8}$ -inch wall is laid out for both centers and soft sides.



**Figure 1-60.** As this exterior wall is built, we see a stud being tilted diagonally and stuffed in the top and bottom plate. Then the stud will be stood upright, and set on layout.



When stuffing studs in a soffit or anyplace the bottom plate will be set to a specific elevation later, cut the studs  $\frac{3}{8}$  inch short, and shove them tight up into the top plate. Soffits and suspension walls are often begun by running the studs wild. They're stuffed in the top plate, then cut to length and plated later. In these situations, it's essential to clamp each stud in place as it's set on layout until they're screwed off.

You've also got to consider cold-rolled channel (CRC) while stuffing studs. CRC is a 16-gauge channel that runs through the stud holes to provide added rigidity or weight support. The stud holes must line up in walls which will receive CRC through the studs, as shown in Figure 1-61. Not all walls require CRC, but always check it out before you start the layout. CRC helps keep the wall straight and resist wind shear. Walls that commonly require CRC are structural stud walls or suspended walls, as well as soffits and wall expansions.

As you stuff walls with CRC, you'll have to lace the CRC as you go. The ends of the CRC need to overlap by 16 inches, as in Figure 1-62. As you stuff the last four to six studs, slide the last stick of CRC loosely into the studs already in place. Once the last studs are stuffed, pull the last stick of CRC through these studs and turn it flat in the stud holes (Figure 1-63). Exterior walls commonly require rows of CRC spaced 4 feet apart, starting at 4 feet above the floor.

In walls where the CRC will carry the weight of the wall via suspension wires, run the CRC through the studs on its edge (Figure 1-64). Under these conditions, the smaller of the two tier stud holes punched in light gauge studs must be up. These holes are designed for the CRC to slide through, to prevent it from sliding around. In suspension work, any movement of the CRC or the suspension wires will affect the elevation of the bottom plate.

## Slap Studs and Sliders


Slap studs (or *sliders*, as they're also called) are used in metal stud framing to form an inside corner where two walls intersect. They allow you to build a solid corner using fewer studs by tying the slap stud of one wall to the drywall of



**Figure 1-61.** Here's a typical  $3\frac{5}{8}$ -inch wall framed up, with all the stud holes lined up.



**Figure 1-62.** You can see the cold-rolled channel run just over a window header (box beam). The CRC joint is overlapped by well over 16 inches, and turned flat in the stud holes.



**Figure 1-63.** Here the CRC is turned flat in the holes of structural studs and welded to the studs — a common practice.



another. I'll cover the "tying in" process in Chapter 13, *Drywall Methods*.

Regardless of the direction of the layout, the hard side of the slider always faces the wall it will later tie into. In Figure 1-65, the first stud of this partition wall is a slider that will tie into a corridor wall. Notice that the slider saves two studs, compared to the same corner framed with wood studs.


I recommend positioning the hard side of the slider  $\frac{3}{4}$  inch off of the intersecting wall, and fasten it in place with a single framing screw at the top plate. This prevents the slider from falling out of the wall and becoming damaged beyond use.

## Notching Plate and Studs for Obstacles


In some framing situations, you'll have to notch the plate or studs for obstacles such as plumbing lines and the red iron of the superstructure. Cut the notches with your snips on light gauge material. Notch heavy gauge material with a chop saw, a Quickie Saw (a chain saw with a chop saw blade), or torch. Any time you've got to notch the framing material for more than a couple of obstacles, notify your foreman. Ideally (which is rare), the studs should run from plate to plate uninterrupted. If a lot of notching is needed, there's most likely a problem that your foreman may need to write an extra work order for.

Use this process to notch either stud or plate:

- ◆ To begin the notch in light gauge material, mark the outside points of the cut with your snips, as shown in Figure 1-66.
- ◆ Next, cut relief cuts approximately 1 inch apart between the marks for the notch (Figure 1-67).
- ◆ At one end of the notch, cut into the hard side of the stud to the required depth, forcing the scrap of the cut up and out of the way, as shown in Figure 1-68.
- ◆ Turn the corner of the notch by simply forcing the snips to turn while cutting. Continue the cut, cutting lengthwise down the hard side of the stud. The relief cuts made earlier will allow the scrap to simply fold out of the way (Figure 1-69).




**Figure 1-64.** Notice the  $\frac{3}{8}$ -inch studs of a large soffit supported by CRC and suspension wires. The small holes on top lock the CRC in place, helping to maintain the elevation and rigidity of the wall.



**Figure 1-65.** Here a short wall is tied to a tall wall using a spreader; the first stud of the short wall is the slider. The slider is turned hard side to the tall wall and left unscrewed.



**Figure 1-66.** Marking the notch with your snips, as shown here, is much faster than measuring and marking the cut with your tape and marker.



**Figure 1-67.** Make the relief cuts in the leg of the stud between the two notch cuts.



**Figure 1-68.** Cutting into the hard side of the stud, beginning at the bottom notch mark.



**Figure 1-69.** The relief cuts allow the scrap stud to roll up out of the way as the notch is cut out of the stud.

- ◆ As you reach the end of the notch, make the second turn and cut back to the outside of the stud to complete the notch. Figure 1-70 shows a completed notch.

To cut structural studs, follow about the same procedure. Mark the notch with a pencil or marker. Then cut the notch using a chop saw or quickie saw. At the two outside points of the notch, cut the stud to the desired depth (Figure 1-71). With these cuts made, bend the scrap over and out of the way, as shown in Figure 1-72. In Figure 1-73, a quickie saw is used to cut the notch lengthwise down the stud, to completely remove the scrap.



**Figure 1-70.** The second turn made cutting back out to the edge of the stud to complete the notch.




**Figure 1-71.** Using a Quickie Saw to make the first two cuts of the notch in a structural stud.



## Deflection Plate

In this unit we'll discuss two styles of deflection plate, their uses, and their framing methods. The deflection plate is designed to allow the roof or deck of a building to move slightly up or down without damaging the wall.




**Figure 1-72.** Once the first two cuts of the notch in this bottom plate were made, the notch was beaten over with a hammer.




**Figure 1-73.** Cutting down the hard side of a structural stud using a Quickie Saw.

*Deep leg plate*, shown in Figure 1-74, is installed just about like the top plate we covered earlier. There are, however, a few significant differences in the techniques used in framing with deep leg plate. First, you'll cut the studs used in the wall 1 to 1½ inches short of the deck (Figure 1-75). The second important issue is the way you screw off the studs to the plate. It's acceptable to screw off only one side of the studs to the deflection plate. Whether you're screwing off one or both sides of the studs, the framing screws will be removed as the wall is "topped out." That's essential to allow the plate to lower without damaging the wall. The drywall is also



**Figure 1-74.** Compare the 6-inch deep leg plate (right) with the standard 6-inch plate (left).



**Figure 1-75.** Studs are cut leaving a 1-inch gap in the top plate. The studs are screwed off on only one side. Those screws will be removed as the wall is rocked.



cut  $1\frac{1}{2}$  inches short of the deck, and isn't screwed to the deep leg plate.

The deep leg plate is used in combination with standard plate when called for in the plans. You plate the deck with the deep leg plate, and then slide standard plate up into the deep leg to carry the studs. Fasten the deep leg plate to the deck. Then slide a stick of standard plate the same width as the deep leg, but with 6 inches cut off the length, up into the deep leg plate (Figure 1-76). The 6 inches you cut off the standard plate will stagger the joints of the plate, making it easier to splice the ends together. Slide the standard plate into the deep leg plate, leaving approximately  $\frac{1}{2}$  inch exposed, and clamp the standard plate in place. Now tack the standard plate to the deep leg plate using the appropriate framing screws. You only need two framing screws per side near each end for each stick of standard plate. Splice both types of plate together as you work down the wall.

In many fire walls using this deflection technique, you'll lay safining insulation (dense fire-rated insulation) in between the two types of plate. Cut the safining insulation into strips that are  $\frac{1}{4}$  inch wider than the plate you're using and approximately 1 inch thick. An old filet knife works great to cut the safining. Slide the strips of safining tightly up into the deep leg plate (Figure 1-77). Insulate only as much of the deep leg plate as you can immediately cover by the standard plate. This keeps the dense heavy insulation in place. Once the safining is in place, slide the standard plate in place and work it like regular plate.

Whether you're installing insulation or not, pull the stud layout, marking it to the exposed lip of the standard plate. Cut the studs to allow  $\frac{1}{4}$  to  $\frac{3}{8}$  inch play between the studs and standard plate. Then stuff the studs on layout and screw them off on both sides (Figure 1-78). The framing screws connecting the two types of plate will be removed by the rockers as the wall is topped out, and no drywall screws will be run into the deep leg plate.

*Accordion plate*, shown in Figure 1-79, can be used in any framing that requires deflection. It's specifically designed to give as the deck settles with the added weight of snow and ice. Work the accordion plate following the same procedures



**Figure 1-76.** This wall is framed to the bar joist using deep leg and standard plate to form a deflection condition. Both sections are spliced, and the lower section is laid out to receive studs.



**Figure 1-77.** The  $3\frac{5}{8}$ -inch-deep leg plate fastened to the bar joist has the safining installed. The second stick of the deflection plate is being installed to hold the dense, heavy insulation in place.



**Figure 1-78.** Here the deflection plate is formed using deep leg plate for both sections of top plate. The layout studs are screwed off to only the lower section of top plate.





outlined in this chapter for shooting up the top plate. Cut the studs to within  $\frac{1}{4}$  to  $\frac{3}{8}$  inch of the first bend in the plate. Once you've stuffed the studs, screw them off on both sides of the plate, using the appropriate framing screws. The framing screws won't be removed with this type of expansion plate.

Both the *deep leg* and *accordion* plate come in 10-foot lengths and are available in various widths.

## Radius Plate

Radius plate is available precut, but you're more likely to cut it from standard plate on the job site, using a chop saw. You can gauge both the depth and spacing of the relief cuts by eye. The relief cuts should come within about  $\frac{1}{8}$  inch from cutting completely through the hard side of the plate. Space the relief cuts approximately 2 inches apart. The 2-inch spacing allows the plate to conform to nearly all radius wall conditions you'll encounter in metal stud framing.

Use the radius plate alone when plating the bottom of radius walls (Figure 1-80). When plating the deck, cut patterns from plywood or drywall (Figure 1-81). The patterns form sections of the radius, which you'll match at the deck to two plumb points per section of plate. Patterns are also a common method of forming radius soffits and suspension walls. We'll discuss them in detail in Chapter 5.

You form radius plate for arches in much the same way. Perforate the standard plate with relief cuts, but you'll cut both legs of the plate and not the back, as shown in Figure 1-82. Cut the radius plate from either structural or light gauge plate with a chop saw. Again, leave about 2 inches between the relief cuts. Make the cuts square across the plate. If they aren't square, the arch will form a twist in it. In Chapter 6 we'll discuss this process in more depth. Making the relief cuts for either of these methods may require rolling the plate up into the blade. To make the relief cuts, keep the material tight to the fence to keep it square with the blade, and move the plate slowly into the spinning blade to avoid the material kicking back.



**Figure 1-79.** This is an end view of a stick of  $2\frac{1}{2}$ -inch accordion plate. The edge of this style of top plate is set to the wall line at the deck just as with any other top plate. Cut the studs to the first bend in the plate and leave the framing screws in as the wall is rocked. The fold in the plate will allow the deflection.



**Figure 1-80.** A standard  $3\frac{5}{8}$ -inch plate with relief cuts made approximately every 2 inches is shot to the floor.



**Figure 1-81.** In this picture, my partner Kelly is clamping the radius plate to the drywall pattern before screwing it off. The pattern will hold the plate in the form of the radius as it's fastened in place to form the top or bottom plate of a drop.



## Fastening the Framing Members

One of the big advantages to building with metal studs, for the carpenter, is the speed and ease of connecting the framing members to each other. Often, a couple of quick cuts with your snips and a few framing screws are all it takes. Here we'll look at three commonly-used methods of fastening the materials together.

You can also use this discussion as a reference for other methods that we'll cover in later chapters. As you work to master these cuts, take your time and be patient. The cuts can be tricky, and are often full of sharp edges. Getting in a hurry or getting mad can get you a nasty cut.


### Shoes

Cut shoes approximately 3 inches from the end on both stud and plate material. Form the shoe by cutting only the legs of the material and then folding back the end (Figure 1-83). In most cases, you can cut the shoe by eyeballing back the 3 inches from the end of the plate and cutting one leg. But if you're cutting shoes on items like headers, the cuts must be square from side to side. If the cuts aren't square across the hard side of the plate, the shoe will cause the header to twist on the stud it's fastened to. For situations like that, square the cut across the hard side of the plate and cut the other leg. Then fold the end of the plate back to form the shoe.


When you're cutting shoes, more often than not there'll be a shoe at both ends of the material you're using. It's common to give and receive measurements for these cuts as "in-between." For example, the direction "40 inches in between" tells you to cut a shoe, then measure 40 inches and cut another shoe.

### Tabs


Tabs are another way you can cut the metal stud material so two pieces can be fastened together (Figure 1-84). Tabs are common on box beam headers, and also to join the intersecting plate of freestanding and suspended wall systems. The length of the tabs will vary, but a 1<sup>1</sup>/<sub>4</sub>-inch tab will do the trick in most situations.



**Figure 1-82.** You can see a stick of 6-inch plate with relief cuts made in the legs of the plate, allowing it to bend and form an arch. The relief cuts were made on a chop saw to keep the cuts square across the plate.



**Figure 1-83.** A shoe cut on the end of a stick of 25 gauge 6-inch plate. Shoes are used on common headers and kickers.



**Figure 1-84.** Here's a tab cut to the end of a 6-inch stud, which is a common fastening point for spreaders and box beam headers.



To cut the tabs, cut through both legs of the material approximately  $1\frac{1}{4}$  inches from the end. Then reposition the material so you can cut down from the end of the material to the first cuts you made in the legs. Cut the tabs with your snips on light gauge material, and use a chop saw on heavy gauge structural material. To make the first cuts  $1\frac{1}{4}$  inches back from the end, set the material in the saw's table and roll it slowly *up into* the spinning chop saw blade. To make the next cuts, reposition either the saw or the material so the saw can cut down the material lengthwise.

## Ears

Ears, sometimes used on headers, work the same as a shoe. Cut the ears exactly backwards from a tab: Leave the legs intact and cut away the hard side of the plate (Figure 1-85). To cut the ears, start at the end of the plate and cut down the break (fold) line approximately  $1\frac{1}{4}$  inches. Now, while slowly cutting, turn your snips and cut across the hard side of the plate. Once the cut across the hard side is complete, make a second turn and cut back out to the end of the plate to finish the ear.

## Kickers and Other Braces


Here we'll cover three commonly-used braces, some of their uses, and how to cut them. These braces are used for everything from supporting to straightening the framing. Knowing without hesitation which brace to use in a given situation is important. Make sure that the kickers or braces you use are either above ceiling height or inside the framing if you're bracing off of another wall or part of the building.

## Kickers

Kickers, like the one shown in Figure 1-86, are useful in countless situations. Use them to brace up freestanding walls, and to straighten as well as strengthen soffits. Cut kickers from stud material, with either one and two shoes cut at the ends. The shoes are often flattened out, with an additional 45-degree bevel cut made to the

end of the stud at the base of the shoe (also visible in Figure 1-86). This bevel cut allows the shoe to sit flat against another surface, such as the top plate of a freestanding wall, or the deck.

When figuring the length of a kicker, it's important to consider the angle the kicker will run at. In order to get the maximum strength from a kicker, it must be set as close to a 45-degree angle as possible. The strength of a kicker is also increased by twisting the kicker, as shown in Figure 1-87. Once you've shot the kicker in place, twist it, then fasten the other end to the framing. Another way to increase the strength of the kicker is by screwing the shoe back together at the 3-inch cut points (Figure 1-88). This little spot is hard to get a screw in. The easiest way to fasten it is to set the shoe at the desired angle and clamp it. Then you'll be able to get a screw in it. It's best to do all of this after the kicker's been fastened in place. Which brings up another point: As you fasten the kicker with either screws or powder-actuated pins, place the screws or pins as close as possible to the fold point of the shoe.



**Figure 1-85.** This shows ears cut on the end of a stick of 6-inch plate. Ears have many uses, but the most common is on common headers on structural framing.



**Figure 1-86.** A simple kicker cut from  $3\frac{5}{8}$ -inch stud. One shoe has been flattened out and beveled to fit flat to the surface it's fastened to.




## Gussets

Gussets are another common style of brace used in the trade. As you can see in Figure 1-89, the gusset is the same as a shoe on the end of a kicker. Gussets are often used to brace furred walls that are built as close as possible to preexisting masonry and precast walls. Cut gussets from scrap stud to whatever size you need. The only side that matters is the one that'll be fastened to the framing. Here's the quickest way to figure it.




**Figure 1-87.** Here's a 3<sup>5</sup>/<sub>8</sub>-inch stud used as a kicker. The stud has been twisted before it was clamped to the wall stud to make it stiffer. In contrast, the kicker next to it hasn't been twisted. Both are shot to the bottom of the bar joist.


Push the end of the scrap stud up against the pre-existing wall, then use your snips to cut both legs at about the center of one of the wall studs, or the bottom plate. The other half of the gusset only has to be long enough to fasten to the preexisting wall. Like the shoe on a kicker, screwing the cut points of the shoe on a gusset will make it a lot stronger. If a stronger gusset is required, cut a short piece of stud with ears and screw it off, running it diagonally inside the gusset (Figure 1-90).



**Figure 1-88.** Here you see the cut points on the shoe of a kicker screwed back together to make the kicker stronger above a door jamb.



**Figure 1-89.** A common gusset cut from 6-inch stud. Rescrewing the legs of the gusset at the cut points will make the brace much stronger.



**Figure 1-90.** Here the gusset itself is braced, making it as strong as a tank. I use this brace on lease (store) walls that will carry shelves full of heavy merchandise.



## The Simple Stud Brace

A simple stud brace is a quick brace that does about the same job as a gusset (Figure 1-91). Cut it from stud material (scrap when possible), then flatten one leg of the stud by hand or with your drywall axe. This allows room to use a shotgun or a screw gun to fasten the brace to the existing wall. The stud brace doesn't provide the strength of a gusset, but it'll make a wall rigid enough for most situations. The biggest drawback of the stud brace is that it's limited to the width of the material it's made from. If there's a 5-inch gap between the new framing and the pre-existing construction, a stud brace made from  $3\frac{5}{8}$  inch stud won't work. Large commercial jobs usually have a wide variety of material sizes available, so you won't have much trouble finding what you need. But don't waste too much time looking around. If you can't find what you need quickly, just cut up a stud and move on!

## Wall Expansions

Wall expansions are a common part of commercial metal stud framing. They're designed to allow a wall to expand and contract without damaging the wall's finish. At the expansion joint, the wall stops and starts again on the other side of a  $\frac{3}{4}$ -inch gap in the framing. You'll lay out the expansion joint as you snap the wall lines, and square it across the corridor when working in a hallway. If this work wasn't done in advance, you should know that an expansion joint is required:


- ◆ every 30 linear feet in walls framed from the floor to the deck
- ◆ every 50 feet on ceilings

If you're working in a hallway, use the 3-4-5 squaring method to make sure the expansions are straight

across from each other. Expansions that aren't square are hardly noticeable — *until* the walls are completed and the grid ceiling is installed. Then, after it's too late, it stands out like a sore thumb!

To frame the expansion, first establish the center of the expansion (if it wasn't done in advance) and measure  $\frac{3}{8}$  inch each way. Plumb these points to the deck, then stop and restart both top and bottom plates at these points. Look at Figure 1-92. The stud layout will also stop and restart at the expansion. Burning 4 inches when reestablishing the stud layout will eliminate a recessed edge of the drywall at the expansion joint. That'll help the trades that follow you.

Set the two expansion studs in the plate, one on each side of the expansion, with the hard side of the studs on




**Figure 1-91.** A scrap piece of  $1\frac{5}{8}$ -inch stud used to form a simple stud brace. Notice that the brace is shot off right into the mortar joint.



**Figure 1-92.** Here's the center of the expansion established at the bottom plate, with the plate stopped  $\frac{3}{8}$  inch short of the expansion center. The studs will be set hard side to hard side, with the studs right at the ends of the plate.



**Figure 1-93.** With the expansion studs stood up and the layout studs in place, pieces of CRC have been cut to span two layout studs on either side of the expansion. The CRC keeps the wall solid at the expansion.



**Figure 1-94.** Here we see the factory edge of a drywall rip set against the outside corner of a column. Then you can grab a drywall screw left sticking out with a pair of end nippers and use it to pull the column out against the rip. Once set, the opposite side of the column corner is screwed off to lock it in place.

the  $\frac{3}{8}$ -inch expansion layout marks. Then stand up two more studs on the layout. Now cut some pieces of CRC, 5 feet long. Slide the CRC through the stud holes, and stop it when it's through the expansion studs and a layout stud on each side. Lace the CRC through the studs every 4 feet, starting at 4 feet off of the other floor, up to the ceiling height. See Figure 1-93. Get the studs screwed off and the CRC turned flat in the stud holes and you're finished. On fire walls, cut strips of fire-rated safining insulation the width of the framing and stuff it in between the expansion studs.

This wall expansion is a great example of why the stud holes should always line up. Imagine trying to install the CRC if they didn't! Now imagine your job site foreman walking by while you're scratching your head. Keep in mind that even though the expansions are an industry standard, they aren't always framed in. The expansions take extra time to frame in, and once one is done, you're committed. So before you take it upon yourself to correct an obvious oversight, consult your job site foreman.

## Straightedging

Straightedging is a commonly-used and widely-acceptable method of transferring a point or wall line quickly and efficiently. A straightedge has many uses, including setting columns and other outside corners as well as finding bumps and dips in walls.

Figure 1-94 shows a drywall rip (the recessed factory edge of a sheet) used as a straightedge to set the outside corner of a column. In Figure 1-95, a level is used as a



**Figure 1-95.** Using a level to transfer the wall line of a wall framed to the bar joist on up to the deck.



straightedge to transfer the wall line of a wall framed to the bottom of the bar joist, on up to the metal roofing. When straightedging on framing material, it's important to watch for one of the two ends of the straightedge resting on a framing screw. Of course, this would throw your point off considerably. As shown in these

examples, the factory edges of a sheet of dry-wall, and levels, make good straightedges. A metal stud also makes a good one. These are just a few examples of straightedging. Given a little time on the job, I imagine you'll find uses I haven't even thought of yet!

Online Preview

# I N D E X

## A

Accessibility for the Disabled Act 6  
Accordion plate 27-28  
Adjustable clip 96  
American-made tools, using 50  
Angle iron 121  
    welding studs to 123  
Arc, striking 69  
Arches  
    cutting archway 92  
    forming radius 93  
    framing 28, 91  
    gyp board, installing 91  
    plating radius 92  
    striking an arc 69

## B

Back blocking joints 136  
Back-cut, drywall 185  
Backing out joints 136  
Bar joist  
    bridging 47  
    plating to 16-17  
    tying hanger wires to 44-45  
    wiring DWC 139  
Basic skills, metal framing 17  
Benchmarks  
    establishing 42-43  
    shooting in 121  
    soffit 56  
Bend point 48-49  
Bending suspension wires 48-49, 172  
Black iron 46  
    lacing with 118  
Black magic markers 121  
Blueprints  
    locating soffit dimensions 55, 151  
    reading 3  
Bottom plate 13-14  
    columns 142, 147  
    corners, forming 79-80  
    distance between pins 78  
    installing heavy gauge 116  
    plumbing soffit corners to 59  
    shooting down 78-80  
    simple framed soffit 160-161  
    skylight 182  
Bottom soffit studs, plating 59, 61-62  
Bound edge, drywall 187  
Box beam header 91, 119  
    building 37-38  
    door jamb 101  
Braces  
    gussets 31  
    kickers 30  
    simple stud brace 32

Bracing  
    studs 110  
    unequal walls 20  
Bracing, diagonal (cross) 127  
Bridging  
    bar joist 47  
    corrugated metal decking 16  
Building methods, steel framing 75-76  
Building with jigs 63-66  
Bulkheads 170  
Bullnose cutters, heavy gauge 11  
Butt joints, coreboard 135

## C

C-clamp 122  
C-H studs 130, 134  
Canopy soffits 69  
Caps, parapet walls 124  
Casework 151  
Ceiling  
    dialing in 175-176  
    elevation, finding for suspended ceiling 175-176  
    framing 42  
    seismic 45  
    stiffbacks 39  
Ceiling systems 171  
    hard lid 177  
    lay-in 176-177  
    suspended drywall 172  
    Rigid X 176  
Certified welder 123  
Chalk lines  
    bottom plate, setting 61-62  
    snapping across long distances 139  
    top plate, setting 125  
    wall layout 6, 78  
Channel thicknesses, DWC 106  
Chase walls 14, 90  
    framing around obstacles 91  
Chop saw, cutting structural studs 116  
Clamps 121-122  
Clean work area, importance of 78  
Clip with straps 96  
Clips 96  
    deflection 116  
    slide 121  
Coffered ceiling 162  
    forming 155  
Cold-rolled channel (CRC) 23  
    at wall expansions 33  
    lacing structural deflection wall 122  
    lacing studs for structural walls 118  
    supporting with suspension wire 46, 49  
    suspended drywall ceilings 45, 173  
    suspension wall studs 168

    tack welding to studs 23, 119  
    tying at corner joints 53  
Color-coding, stud gauge 115-116  
Columns  
    bottom plate 142  
    concrete, framing around 109  
    corner guards 144  
    drywall, framed 146-149  
    drywall ribs 148  
    establishing frame line 142  
    framing 141  
    framing cornice 144-145  
    lookouts 142  
    speed-framed 146-149  
    three-sided 146-149  
Computer floors 43  
    door jambs, installation 100  
Concrete  
    columns, framing around 109  
    decks 15  
    piers, column 142  
    truss systems 15-16  
Concrete pins 118  
Conduit rack, headering 37  
Connecting framing members 29  
Control stud, horizontal 59  
Coreboard 131  
    backing joints 135  
    staggering joints 135-136, 137  
    standing 133-135  
Corner guards, column 144  
Corner jigs, setting 163  
Corner soffit studs, plumbing 58-59  
Corners, blowing out 108  
Corners, forming 14-15, 17-20  
    bottom plate 20, 79-80  
    CRC 53  
    fire-rated walls 137  
    freestanding walls 88-89  
    hard 116  
    intersecting walls 18-19  
    parapet walls 126  
    setting with a rip 187  
    shaft wall 132-133, 135  
    shooting to DWC 108  
    top plate outside 18  
    tying to preexisting condition 20  
    unequal walls 18-19  
    utility angle 44  
Cornice, framing for column 144-145  
Cornice studs 146  
Corrugated metal decking 16  
Crew requirements, plating 14  
Cripples  
    double cutting for CRC 120  
    framing 85  
    installing door jamb 99  
    installing window jambs 104  
Cross bracing 127  
Cross channel 177





Cross tees 177  
 Crown cornice, stair step 144-145  
 Cutting  
   archway 92  
   box beam header 37-38  
   coreboard 131  
   door studs 98  
   drywall 184-186  
   ears 30  
   ears for header 36  
   hand 10  
   radius plates 28  
   rips 138  
   shoes 29  
   shoes for header 35  
   soffit patterns 69  
   structural studs 116  
   studs, walls to the deck 82-83  
   tabs 30  
   templates 70

**D**

Deck  
   concrete 15  
   framing soffit to 57  
   metal 16  
   plating 15  
 Deck punch 45  
 Decking screws, fastening with 16  
 Deep leg plate 26-27  
   framing shaft walls 130  
 Deflection clips 116  
 Deflection plate 116  
   accordion 27  
   deep leg 26  
 Deflection wall, structural 121  
   lacing with CRC 122  
 Detail drawings 3  
   symbols 3-4  
 Diagonal braces  
   cross bracing 127  
   unequal walls 20  
 Dialing in ceiling 175-186  
 Door headers 36  
 Door jambs  
   computer floor installation 100  
   fastening 98  
   headers 99  
   headering underneath 100, 101  
   leveling 97  
   one-piece 95  
   print numbers 97  
   setting 97  
   shimming 97-98  
   stiffening with kickers 100  
   suspended 101  
   three-piece 95  
   tight fitting 101-102  
 Door studs 98  
 Doors, entry 120  
 Doors, laying out 7  
 Double inside corner, plating 14-15  
 Double-duty dryline 62  
 Drain racks, framing around 90-91  
 Drawings, detail 3  
 Drop  
   framing 55, 151  
   framing with jigs 162  
   kicker jigs 163  
   light trough 161  
   setting corner jigs 163

to suspended ceiling 156  
 utility angle 164  
 Dryline  
   plumbing with 59, 60-61  
   setting for freestanding walls 88  
 Drywall  
   archways, installing over 91-92  
   back-cut 185  
   brace 110  
   corners 108  
   corners, fire-rated walls 137  
   cutting with router 186  
   cutting with utility knife 184-185  
   fastening 187-188  
   fire taping 142  
   hanging 187  
   installation 183  
   marking 184  
   rips, cutting 138  
   scoring 185  
   setting outside corners 187  
   soffit support 74  
   templates, soffit 69  
   thickness, planning for 6  
   tying in slap studs/sliders 189-190  
 Drywall ceiling systems 171  
   framing 41  
   hard lid 177  
   lay-in 176-177  
   suspended drywall 172-175  
   Rigid X 176  
 Drywall channel (DWC)  
   furring with 106  
   installing fire lids 139  
   layout 106  
   shooting to wall 107  
   suspended drywall ceiling 174-175  
 Drywall framed columns 146-149  
 Drywall screws, laminating 136  
 Ductwork, headering around 37, 84-85

## E

E-stud 133  
 Ear protection 72  
 Ears, cutting 30  
   on headers 36  
 Electrical boxes, cutting out 186-187  
 Elevation  
   ceiling 42-43  
   computer floors 100  
   deflection wall 121  
   hard lid ceilings 178  
   parapet walls 124  
   plate line for suspension wall 169  
   soffit 56  
   spanning speed soffit 152  
   suspended ceiling 53-54  
   suspended drywall ceiling 172  
 Elevator shaft liners 130, 131  
 End nippers 50, 187  
 End studs, shooting in place 86  
 Equal elevation walls, forming corners 18  
 Expansion joints, wall 32  
 Expansion plate 26  
 Exterior walls  
   chalking 6  
   furring with Z-channel 111  
 Exterior window openings, framing 119  
 Eye protection 72

## F

Factory spreader 99  
 Fastening  
   door jambs 98  
   DWC 107  
   framing members 29  
   heavy gauge materials 116  
   joints, top plate 88  
   kickers, top plate 88  
   plate 13  
   RC channel 113  
   soffit studs 59, 61-62  
   studs 84  
 Fastening ceiling materials  
   screw method 52  
   tie wire method 50-51  
 Finished wall dimensions 6  
 Fire containment systems 130  
 Fire extinguishers, layout for 7  
 Fire lids 138  
 Fire-rated ceilings 138  
   installing utility angle 140  
   taping drywall 142  
   tying up DWC 139  
 Fire-rated jambs 95  
 Fire-rated walls 129, 136  
   framing 17  
   installing safing insulation 27  
   rocking corners 137  
 Five-siding electrical boxes 129  
 Floating end soffit 154  
 Forming corners, bottom plate 79-80  
 Four-step method, obstacle layout 7-8  
 Frame line, column 142  
 Framed soffit 158  
   bottom plate 160-161  
   inside plate 160  
   kickers 159  
   layout 158  
   outside corner 161  
   studs 159-161  
   top plate 158  
 Framed to the deck, chase walls 90  
 Framing  
   arches 28, 91  
   around concrete columns 109  
   bottom plate 13-14  
   box beam headers 37-38  
   chase walls 90  
   columns 141  
   columns with drywall 146-149  
   corners 17-20, 88  
   cornice to column 144-145  
   cripples 85  
   door jambs 96  
   drywall ceiling 41  
   fastening to concrete decks 16  
   fire-rated ceiling 138  
   fire-rated walls 17, 137-138  
   freestanding walls 86  
   furred walls 105, 109  
   hard corners 116  
   hard lid ceilings 177  
   headers 35, 85  
   interior walls 77  
   large windows 104  
   light trough 161  
   lookouts 71  
   metal decking 16  
   multilayer walls 80  
   parapet wall to red iron 126



parapet walls 123  
 radius soffits 69-70  
 radius walls 28  
 Rigid X system 176  
 shaft liner systems 130  
 skylights 179  
 smoke walls 17  
 soffit to deck 57  
 soffits 55, 151  
 soffits with jigs 65-66  
 sound walls 17  
 spacing for drywall 15-16  
 spanning gaps with spreader 19-20  
 spanning speed soffit 152  
 structural deflection walls 120  
 structural exterior walls 116  
 structural stud walls 115  
 structural wall rough openings 119  
 stud layout 21-22  
 stuffing studs 22-23  
 suspended bottom plate 59, 61-62  
 suspended drywall ceilings 172  
 suspended speed soffit 155  
 tools 42  
 top plate 15  
 unequal wall corners 20  
 using CRC 23  
 using deep leg plate 26-27  
 wall corners 14-15  
 wall expansions 32-33  
 windows 102  
 with jigs 56

Framing, metal, advantages 1

Freestanding walls  
 bracing studs 110  
 fastening top plate 86-87  
 framing 20, 86  
 framing corners 88  
 installing jamps 89-90  
 installing kickers 87-88  
 setting corners 88-89  
 setting ends 86  
 stud layout at top plate 87

Full-framed columns 142

Furred walls 105

Furring  
 inch 'n five studs 109  
 RC channel 112-113  
 Z-channel 111

Furring methods, DWC 106

## G

Gang box 118

Gap, setting  
 door jamps 98  
 window jamps 103

Gas-actuated nail set 15  
 assembly 107  
 using 78

Gauge block 62

Gauge, metal studs 62  
 structural 115

Gospel line, establishing 6  
 skylight layout 179

Green-handled snips 10

Grid ceilings 4, 176

Gusset 31  
 bracing top plate 110

Gyp board, installing over archways 91-92

## H

H studs 130, 134

Hallways, laying out 6

Hammer drill, using 78

Hand cutting, plates and studs 10

Hanger wires  
 CRC, suspension walls 168  
 suspended drywall ceiling 172  
 tying up 44

Hanging drywall 187

Hard corners, framing 116

Hard lid ceilings 39, 177  
 framing rough openings 179  
 installing stiffback 178-179  
 installing studs 178  
 plating 178  
 reflective ceiling plan 4

Hard number 82

Harness 121

Hat channel 52, 106  
 suspended drywall ceiling 174-175

Hat channel head, shotgun 106

Hat track 106

Headers  
 around obstacles 36-37, 84  
 bottom plate, chase walls 91  
 box beam 37-38, 91  
 door 36, 99-100  
 framing 85  
 laying out 35  
 structural 36  
 window 39, 103

Heavy-gauge material, splicing 12

Hi-lo plate 130

Hollow metal jamps 95

Horizontal control stud 59  
 skylight 181

Horizontal welds, studs 123

Hourly wage, metal frame  
 construction 2

HVAC shaft liners 130

HVAC systems, framing around 41

## I

"In between" measurements 29, 35, 85

Inch 'n five studs  
 bracing top plate 110  
 furring with 109

Inside corners  
 drywall 189-190  
 plating 14-15  
 shooting DWC 108

Inside plate, simple framed soffit 160

Installing clips 96

Installing studs 22-23, 83-84

Insulating Z-channel 111-112

Insulation  
 between plates 27  
 safig 27  
 sound 112

Interior walls  
 chalking 6  
 corners 18-19  
 framing 77  
 intersecting walls 23-24  
 types 78-79

## J

J-mold 158

J-runner 130

Jamps  
 door 97  
 hollow metal 95  
 installing in freestanding walls 89-90  
 installing in lead-lined walls 96-97  
 measuring for consistent elevation 7  
 tight-fitted 101-102  
 window 102-104

Jig, building 63-64

Jigs, soffit 162  
 framing with 56  
 kicker 163  
 plumbing 68  
 setting 66

Joining plates 11-12

Joining studs 29

Joints  
 fire taping 142  
 suspended ceiling 52

## K

Kickers 30  
 jigs 163  
 reinforcing spanning soffit 154  
 simple framed soffit 159  
 soffit 60  
 stiffening jamb with 100  
 support for freestanding wall 87-88  
 suspension walls 168

King studs 98  
 installing tight-fitted jamps 102

## L

L-metal 158

Lacing studs 118

Laminating drywall screws 136

Lanyard 121

Large jamps, window 104

Laser 43  
 plumbing exterior walls 116-117  
 soffit framing 57-58  
 suspended ceiling installation 54

Laser card 167

Laser, pocket 152

Lath screws 44, 116

Lay-in ceiling 176-177

Laying out patterns 69-70

Layout  
 around obstacles 7-8  
 column 142, 147  
 door 7  
 drop for light trough 162  
 drywall 21  
 DWC 106  
 fire lid, DWC 139  
 hat channel 106  
 recessed items 7  
 shaft wall 131  
 simple framed soffit 158  
 skylight 179  
 soffit 55-56  
 soffit lookouts 72  
 structural deflection wall 121  
 wall 6  
 window 7



Layout jigs 164  
 Lead-lined walls  
   door jambs 96-97  
   window jambs 104  
 Left-cut snips 10  
 Legend, wall 3-4  
 Lengths, light gauge studs 77  
 Levels  
   magnetic 97  
   torpedo 146  
   water 42  
 Lifts, working off 166-167  
 Light gauge studs, basic widths and lengths 77  
 Light trough 161  
   framing with jigs 162  
   installing utility angle 164  
   kicker jigs 163  
   layout jigs 164  
   plating 164-166  
   setting corner jigs 163  
 Lineman's pliers 176  
 Long studs, standing 122  
 Lookouts  
   column 142  
   column cornice 145  
   soffit 71-72  
 Lumber prices, instability of 2

## M

Magnetic level 97  
 Mains, suspended ceiling 177  
 Marking  
   drywall sheets 184  
   studs, gauge 115-116  
   wall layout 7  
 Masonry  
   fastenings studs to 86  
   shooting DWC to 108  
 Material, storing/stocking 78  
 Measurements, "in between" 29, 35  
 Measuring, right angles 5  
 Metal decking 16  
 Metal framing  
   advantages 1  
   price stability 2  
   skills required 17  
   wages and benefits 2  
 Metal jambs, hollow 95  
 Metal scoring 11  
 Metal stud walls  
   framing 77  
   structural 115  
 Metal trim 158  
 Methods, framing 75-76  
 Minimizing waste, importance of 77  
 Mullions, framing to 120  
 Multilayer walls, framing 80  
 Multiple plate lines 80

## N

90-degree plumb marks, using 81  
 Notations, print 3  
 Notching plates/studs 24

## O

Obstacles  
   framing chase walls 91

  headering around 36-37, 84-85  
   notching plates or studs for 24  
   planning layout around 7-8  
   plating around 80  
 Offset plate elevation walls, forming corners 18-19  
 Offset plate lines 80  
 One-piece door jambs 95  
 Openings, liners for 130  
 Outside corners  
   bottom plate 20  
   setting with a rip 187  
   shooting DWC 108  
   simple framed soffit 161

## P

Pan-head screws 13  
 Parapet walls  
   establishing elevation 124  
   framing 123  
   framing to red iron 126  
   intersecting walls 126  
   plating the studs 124  
   setting the plate 125-126  
 Patterns, soffit 69  
 Piers 116  
 Pins  
   concrete 118  
   sheared 109  
   steel 118

Pipes, headering around 84-85  
 Pivot point, arch 92  
 Planning, importance of 77-78  
 Plate line elevation  
   establishing 57  
   setting 169

Plate lines  
   multiple 80  
   offset 80

Plates  
   bottom 13-14  
   cutting 10  
   deep leg 26-27  
   deflection 26-28  
   hi-lo 130  
   inside 160  
   insulation between 27  
   laying out 21  
   notching 24-25  
   radius 28  
   shaft liner 130  
   shooting 13  
   splicing 11-12

Plating  
   arch radius 92  
   around obstacles 80  
   bottom studs, soffit 59, 61-62  
   deck 15  
   hard lid ceilings 178  
   inside corners 14-15  
   light trough drop 164-166  
   red iron 117  
   studs, parapet walls 124  
   suspended speed soffit 156-157  
   teamwork 78  
   to bar joist 16-17

Plumb bobs  
   custom 121  
   using 8  
 Plumbing  
   jambs 98  
   plate line, column lookouts 143

  soffit 58-59  
   structural walls 116-117  
   suspension walls 167  
   techniques 8-9  
   wall lines 81  
   with dryline 60-61  
 Plywood spreader 99  
 Plywood templates, soffit 69  
 Pocket laser 121, 152  
   plumbing with 9  
 Pony clamp 124  
 Powder-actuated nail set  
   assembly 106  
   cleaning 106-107  
   plating with 14-15  
   using 78  
   with hot channel head 106  
 Preexisting condition, tying to 20  
 Prefab shaft liner corner 133  
 Prepared wall mold 176  
 Prepping work area 78  
 Price stability, metal framing 2  
 Prices, wood products 2  
 Print notations 3  
 Print numbers, jambs 97  
 Protrusion framing 71  
 Pulling layout 22  
   stud layout, offset walls 80

## Q

Quality work, importance of 77  
 Quality, wood products 2  
 Quickie Saw 24  
   cutting structural studs 116

## R

Racking, prevention of 127  
 Radius plate 28  
 Radius plate bender 93-94  
 Radius soffit patterns 69-70  
 Razor knife 158  
   scoring with 186  
 RC channel 112-113  
 Reading blueprints 3  
 Recessed edge 187  
 Recessed items, wall layout 7  
 Recessed lights, cutting out 186  
 Red iron  
   building columns around 142  
   forming parapet walls 126  
   piers 116  
   plumbing to top piece 121  
   superstructure, fastening to 17  
 Red-handled snips 10  
 Reference lines, establishing 6  
 Reflective ceiling plans 4, 41  
 Reinforcing wall studs 23  
 Relief cuts, radius plates 28  
 Resilient furring channel 112-113  
 Rest rooms, framing chase wall 90  
 Right angles, establishing 4-5  
 Right-cut snips 10  
 Rigid X system 176-177  
 Rips 138  
   bottom, suspended soffit 157  
   spanning speed soffit 152  
   speed-framed column 148  
   vertical face, suspended soffit 156  
 Rock to rock screws 136

Online Preview



Styrofoam insulation 111-112  
 Superstructure, fastening to 17  
 Suspended ceilings  
   adding extra support 53  
   establishing elevation 42-43  
   fastening joints 52  
   fastening with screw method 52  
   fastening with tie wire method 50-51  
   forming corners with CRC 53  
   framing 41  
   tuning in elevation 53-54  
   tying suspension wires 44  
   utility angle 44  
 Suspended doors, installing 101  
 Suspended drywall ceiling  
   adjusting ceiling elevation 175-176  
   establish elevation 172  
   hanging suspension wires 172  
   installing CRC 173  
   installing DWC 174-175  
   installing utility angle 172  
 Suspended framing, bottom studs 59,  
   61-62  
 Suspended speed soffit 155  
   hanging vertical face ribs 156  
 Suspension trapeze 47  
 Suspension walls 166  
   framing corner 20-21  
   kicking off 60  
   lacing CRC 168  
   plating studs 169  
   plumbing with laser 167  
   setting plate line elevation 169  
   supporting CRC 168  
 Suspension wires  
   bending 48-49  
   bridging bar joist 47  
   locking into place 54  
   Rigid X system 176-177  
   splicing 46  
   stretching 47-48  
   supporting CRC 23, 49  
   suspended drywall ceiling 172  
   tying to bar joist 44-45  
 Swing, door 97  
 Symbols, detail 3-4

## T

T-square 185  
 Tab method, top plate fastening 16  
 Tabs, cutting 30  
 Tags, jamb 97  
 Tap-con system, concrete fastening 78  
 Tape and pencil, marking with 184  
 Teamwork, plating 78  
 Tek screws 16  
 Templates  
   cutting 70  
   radius plates 69  
 34s 116  
 3-4-5 squaring method 4-5  
 Three-piece door jambs 95  
 Three-sided column 146-149  
 Tie wire method, fastening ceiling  
   materials 50-51  
 Tight-fitted jambs 101-102  
 Tissue dispensers, layout for 7  
 Tools, American made 50

Top out 85  
 Top plate  
   bracing 110  
   column 143  
   forming outside corners 18  
   freestanding walls 86, 88  
   light trough drop 162  
   shaft wall 132  
   shooting 15  
   simple framed soffit 158  
   skylight 181  
   snapping line 81  
   structural steel walls 117  
   suspension walls 167  
 Torch, cutting with 116  
 Torpedo level 146  
 Track, splicing 11-12  
 Trade tricks, metal framing 1-2  
 Transferring a wall line 33-34  
 Trapeze, suspension 47  
 Tricks of the trade 1-2  
 Trim metal 158  
 Tying  
   metal framing 11-12  
   rock to truss 138  
   suspended ceilings joints 52  
   suspension wires 44-49

## U

Unequal walls, bracing 19-20  
 Utility angle  
   arch 93  
   fire-rated ceiling 140  
   light trough 164  
   suspended ceiling 44  
   suspended drywall ceiling 172  
 Utility knife 131  
   cutting drywall 184

## V

Vertical face ribs 156  
 Vertical face soffit studs 153  
 Vertical stud welds 123

## W

Wages and benefits, metal construc-  
   tion 2  
 Walk-up 107  
 Wall angle 44  
 Wall dimensions, blueprints 6  
 Wall expansions 32  
 Wall legend 3-4  
   material requirements 80  
 Wall lines  
   chalking 78  
   chalking both sides 6-7  
   plumbing 81  
   transferring 33-34  
 Wall mold, pre-painted 176  
 Wall types 78-79  
   chase 14  
   fire 130  
   freestanding 20  
   glass and mullion 120  
   to the deck 78

## Walls

  corner framing 14-15  
   exterior, furring with Z-channel 111  
   forming corners 17-20  
   furred 105  
   laying out 6  
   lead-lines 96-97  
   rigidity, increasing 110  
   stud layout for drywall 21  
   suspension, kicking off 60  
 Walls to the deck 78  
   cutting studs to length 82-83  
   ending the wall 86  
   headering for obstacles 84  
   plumbing wall lines 81  
   shooting bottom plate 78  
   shooting top plate 82  
   stud layout 82  
   stuffing the studs 83-84  
 Waste, minimizing 77  
 Water level, using 42  
 Welding  
   CRC 23, 119  
   cross bracing 127  
   slide clips 122  
   structural walls to red iron 123  
   studs to angle iron 123  
 Wheelchair accessibility 6  
 Widths, light gauge studs 77  
 Wind factor, plumbing walls 116-117  
 Window jambs 95  
   cripples 104  
   headers 36, 103  
   installing studs 103  
   lead-lined 104  
   setting 102  
 Window studs 98  
 Windows  
   large 104  
   laying out 7  
 Wire tier 44  
 Wires, suspension 44  
   saddle tying CRC 168  
   suspended drywall ceiling 172  
 Wiring, drywall to truss 138  
 Wood prices, instability of 2  
 Work area  
   cleaning 78  
   laying out 6  
 Work quality, importance of 77

## X

X-bracing 127  
 X-ray room walls 96-97

## Y

Yellow-handled snips 10

## Z

Z-channel  
   furring with 111  
   installing insulation 111-112